

Specification & Submittal Form Cranked Grab Bars

ARC, Inc. I-877-319-6521 info@arcfirst.net

- I. General Description
 - a. Offset hand hold device
- 2. Item Codes and Descriptions
 - a. 01750 . . . 24" cranked grab bar
 - b. 01760 . . . 18" cranked grab bar
- 3. Physical Characteristics
 - a. Made of cold drawn mild steel tube
 - b. Protected with polyester epoxy powder coating
 - c. Finishing process includes rust inhibitor treatment
 - d. Grip diameter: I"
 - e. Distance from grab bar to wall: 2"
 - f. Color: white
 - g. 2 mounting holes at each end
 - h. Mounting flanges are offset from grip area
 - i. 275 lb. load rating when properly fastened
 - j. Fasteners not included
 - k. Use of #10 round head fasteners recommended (use stainless fasteners for wet area installations)

4. Performance Characteristics

- a. Offset design allows user to step through a doorway without releasing grip
- b. Narrow mounting profile allows installation where other grab bars won't fit
- c. For indoor use
- d. Must be fastened to properly installed wood blocking, studs, or other substantial material

5. Other Information

- a. Conforms to 96 hour salt spray test (ASTM B117-87)
- b. 10 year limited warranty for residential use
- c. 5 year limited warranty for commercial use

