

1363BFC2PMA

521 CMR Compliant*

CUSTOMER:	STANDARD FEATURES	
JOB NAME:	 Code compliant when fully equipped and installed according to guidelines 2-piece Pre-leveled base Center drain location 	
PO #:		
QUOTE #: QUANTITY:	Slip resistant, textured bottom [ASTM F-462]	
SHIP TO: PLUMBING CONTRACTOR APPROVAL DATE	CONFIGURATION Fully equipped-521CMR* Seat location LH RH Includes two 30" x 11/4" diameter etched grab bars; white-cushioned, rectangular fold-up seat; pressure balancing mixing valve and hand-held shower assembly (on back wall offset seat), per 521 CMR guidelines	
GENERAL CONTRACTOR APPROVAL ENGINEER APPROVAL ARCHITECT APPROVAL DATE	CUSTOM OPTIONS (not available if 521 CMR config. is selected) Fixture Wall	
ADA compliant showers with NO interior threshold will have water escape onto the bathroom floor. Aquatic highly recommends you take the following precautions:	OPTIONAL ACCESSORIES (available for all models) Soap dish Curtain rod Shower curtain Vinyl flexible dam Removable threshold Brass drain Colors:	ICC FS PMG
 Install only the minimum number of ADA units without an interior threshold required for each job. If possible install Aquatic's accessible models that have a ½" interior threshold to reduce the amount of water that escapes from the shower. When installing units with NO interior threshold, install a <u>FLOOR DRAIN</u> to control the water that escapes onto the bathroom floor. Depending on your application, you may choose to install Aquatic's vinyl flexible dam or removable threshold, which helps better retain water within the shower. However, these items may not necessarily meet ADA or other code requirements. Always confirm code compliance with your local building authority. 	Standard	Int. Dim. 36 W x 36 D x 75 % H Ext. Dim. 39 W x 38 % D x 77 % H Skirt Ht. ¾ skirt, NO interior threshold Packaged Wt. 182 lbs. gross Material AcrylX™ applied acrylic Warranty AcrylX™ Finished Products — Lifetime Limited (30 year commercial)

To complete your order, this document must be signed and faxed to the Aquatic Centralized Customer Service Center.

Fax (866) 544-5353 • Phone (800) 945-2726

Please indicate changes needed.



