

MONTERREY™ 0.35 GPM

TWO-HANDLE 8" WIDESPREAD LAVATORY FAUCET


WITH CONVENTIONAL SPOUT



MODEL NUMBER:

6500.174 Widespread Lavatory 0.35 gpm Pressure Compensating, Vandal-Resistant Non-Aerated Spray. Vandal-Resistant Wrist Blade

handles. Less drain and pop-up hole.



GENERAL DESCRIPTION:

Durable cast brass construction throughout. Cast brass valve bodies with 8" rigid copper connection with compression fittings. 1/2" male threaded inlet shanks with brass coupling nuts. 1/4 turn ceramic disc valve cartridges. Vandal-Resistant Wrist Blade handles with blue & red color indexes. 0.35 gpm/1.3L/min. maximum flow rate.

PRODUCT FEATURES:

Meets CALGreen: 0.35 gpm/1.3 L/min. flow rate

Pressure Compensating Spray: Provides a constant water flow of 0.35 gpm throughout the pressure range

Solid Brass Construction: Durable - Excellent in high use applications. Ideal for prolonged contact with water.

Ceramic Disc Valve Cartridges: Assures a lifetime of drip-free performance.

Lead Free: Faucet contains ≤ 0.25% total lead content by weighted average.

SUGGESTED SPECIFICATION:

Two handle widespread lavatory faucet shall feature cast brass valve bodies with 8" rigid copper connection. Shall feature water-conserving pressure compensating, vandal-resistant 0.35 gpm/1.3L/min. non-aerated spray. Vandal-Resistant Wrist Blade handles. Shall also feature 1/4 turn washerless ceramic disc valve cartridges. Fitting shall be American Standard Model # 6500.174.002.




MONTERREY™ 0.35 GPM

TWO-HANDLE 8" WIDESPREAD LAVATORY FAUCET WITH CONVENTIONAL SPOUT

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A117.1 ASME A112.18.1 CSA B 125 NSF 61/Section 9 and Annex G CALGreen



		Finish
Product		Polished Chrome
Number	Description	002
6500.174	Widespread Lavatory. 0.35 gpm/1.3L/min. pressure compensating vandal-resistant non-aerated spray. Vandal-Resistant Wrist Blade Handles. Less drain and pop-up hole.	

MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES