



PRODUCT FEATURES:

- **Self-Adjusting Sensor:** Sensor automatically sets the activation range on start-up by evaluating sink size and other factors. Will adjust range to adapt to changes in the bathroom environment.
- **Sensor in Spout Tip:** Clean, streamlined style. Hidden sensor reduces vandalism.
- **Hygienic, touch-free operation**
- **Self-Cleaning Solenoid Reduces Maintenance:** Integral wiper spring prevents clogging and run-on.
- **Easy to Service Integrated Strainer:** Patented in-line strainer protects the solenoid from debris. Strainer is enclosed in removable debris cup for easy service.
- **Safety Timer:** Helps prevent vandalism by turning off the faucet if the sensor is blocked for 55 seconds.
- **Fail-Safe:** Faucet automatically shuts off upon loss of power or dead battery. Prevents costly excess water usage and potential flooding.
- **Lead-Free:** Faucet contains ≤ 0.25% total lead content by weighted average.

GENERAL DESCRIPTION:

Deck-mount electronic faucet with proximity operation. Vandal-resistant brass construction with single-post mounting. Operates on DC (battery) or AC permanent power. Water pressure range from 20 - 120 psi. Single inlet. 18" flexible stainless steel inlet hose with 3/8" compression fitting for inlet to control box.

MODEL NUMBER:

■ **PWRX™ 10 YEAR BATTERY POWERED**

- 2064.146** 0.35 gpm/1.3 L/min PCA, VR multi-laminar spray.
- 2064.145** 0.5 gpm/1.9 L/min PCA, VR multi-laminar spray.
- 2064.142** 1.5 gpm/5.7 L/min PCA, VR laminar flow outlet.

■ **DC (CR-P2 LITHIUM BATTERY) POWERED**

- 2064.156** 0.35 gpm/1.3 L/min PCA, VR multi-laminar spray.
- 2064.155** 0.5 gpm/1.9 L/min PCA, VR multi-laminar spray.
- 2064.153** 1.5 gpm/5.7 L/min PCA, VR laminar flow outlet.

■ **OPTIONAL 4" or 8" Deck plates**

- 206P.400** 4" brass deck plate
- 206P.800** 8" brass deck plate

■ **OPTIONAL Thermostatic Mixing Valve**

- 605XTMV1070** Thermostatic mixing valve, 20" long flexible stainless steel inlet hoses with 3/8" compression fitting. ASSE 1070 certified down to 0.35 gpm/1.3 L/min.

*PCA - Pressure Compensating

POWER OPTIONS:

- **PWRX 10 Year Battery System:** 480,000 cycles (10 years @ 4,000 cycles per month). Advanced battery & electronics reduce the downtime and maintenance costs associated with changing batteries. Safety Circuitry prevents overheating in case of short circuit and protects the electronics from damage.
- **DC (Battery):** Includes CR-P2 lithium battery. Battery Life - 192,000 cycles (4 years @ 4,000 cycles per month).



RECOMMENDED SPECIFICATION:

Electronic, sensor-operated proximity lavatory faucet shall feature vandal-resistant brass body with single-post mount design and single inlet. Shall also feature a low energy use electronically operated solenoid valve with an in-line strainer, and microprocessor controlled proximity sensors. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Model shall be American standard # 2064.1____.

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

- ANSI A117.1**
- ASME A112.18.1**
- CSA B 125**
- NSF 372**

ADA Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for accessible and usable building facilities - check local codes

Finishes	
Polish Chrome	002
PVD Satin Nickel	295

