

The American Standard $30'' \times 52''$ Gelcoat walk-in bath provides a similar bathing experience to larger models but fits in smaller spaces and uses less water. The included tub extender allows this tub to retrofit in the same space as a standard bathtub. The full sized, contoured door with a low door threshold allows ease of entry and exit.

Fully equipped, the 609 Value Series offers all the latest in safety and comfort features with the most advanced therapeutic options and backed by a lifetime warranty on the door seal, a 10 year warranty on the tub shell and a 5 year warranty on all other components.

Experience a soft and caressing

Whirlpool Massage



A soothing and invigorating water jet massage system, the Whirlpool massage features an in-line heater and Legs-Only massage. Customize back and leg muscle therapies with 8 different water jets. The Whirlpool Spa is combined with all of the features of the Soaker Tub providing an enhanced therapeutic bathing experience.

Air Spa Massage



all-over body massage powered by a single speed heated blower that releases thousands of air bubbles rising throughout the water from 21 different air jets. The automatic purge cycle helps keep the system running efficient and clean. The Air Spa is combined with all of the features of the Soaker Tub providing an enhanced therapeutic bathing experience.

Combination System





Combines all of the features of the Soaker Tub, the Whirlpool Massage and the Air Spa Systems, plus a multi-colored Chromatherapy light system for the ultimate therapeutic bathing experience.

Quick Drain® System



Spend less time waiting with this patented innovation, that requires no additional plumbing, once activated it rapidly pumps the water out from within the tub-making it safe to open the door and exit the tub. Included in all systems.

3052.609 VALUE SERIES 30" X 52" WALK-IN BATH

3052.609.SXX Soaking Tub

- Tub Extender Kit to fill 60" space
- Available in White or Linen and in Left Hand or Right Hand Door/Drain Configuration
- Watertight door system with a lifetime warranty on the door seal
- Built-in chair height seat
- · Color matched trim and cable driven waste and overflow
- · Built-in safety bar and textured tub floor
- · Cushioned neck rest
- Patented Quick Drain® fast water removal system
- · Premium fast-fill tub faucet and handheld showering wand

3052.609.WXX Whirlpool Massage System Combines all of the features of the Soaking Tub, plus:

- 8 massage jets with variable flow
- Legs-only massage
- · Whirlpool in-line heater

3052.609.AXX Air Spa System Combines all of the features of the Soaking Tub, plus:


- 21 seat and floor air injectors
- · Single speed heated blower
- · Automatic purge cycle


3052.609.CXX Combination System Combines all of the features of the Soaker Tub, the Whirlpool Massage and the Air Spa Systems for the ultimate therapeutic bathing experience, plus:

 Multi-colored Chromatherapy light system positioned at the bottom of the bath that creates a peaceful bathing experience



Products with the Arthritis Foundation's Ease of Use[™] Commendation are tested and proven to make daily tasks easier. Learn more at arthritis.org/easeofuse.





| GENERAL SPECIFICATIONS FOR 3032.009.XXX | |
|-----------------------------------------|----------------------------------------|
| WALK-IN BATHTUB | |
| INSTALLED SIZE | 52 x 30 x 42 ln. (1321 x 762 x 1067mm) |
| WEIGHT | 138 Lbs. (62 Kg.) |
| WEIGHT w/WATER | 904 Lbs. (410 Kg.) |
| OPERATING GALLON | 60 Gal. (227 L.) |
| FLOOR LOADING | 85 Lbs./Sq. Ft. (408 Kgs/Sq. m.) |
| (PROJECTED AREA) | |
| | |

CENEDAL SPECIFICATIONS FOR ZOE2 600 VVV

To Be Specified - Required:

☐ Drain Configuration: Left (L) or Right (R)

☐ Color: White (W) or Linen (L)

Options:

CUBE (FT3) _

☐ Handshower Glide Bar: 9HSB☐ 24 inch Grab Bar: 9GB-24

Notes: The whirlpool heater is designed to maintain water temperature during operation. It will not heat cold water to desired bathing temperature. Tub is supported by the frame and five integrated adjustable feet, no additional support required. Refer to installation instructions supplied with tub for additional information. Provide suitable reinforcement to sub floor for all supports.

Our products are in compliance with the following codes: Uniform Plumbing Code UPC*; National Plumbing Code of Canada; International Plumbing Code IPC*

Our products conform to the following standards: ASME A112.19.7, ASME A112.19.15; CSA B45, CSA B45.5; CSA C22.2 No. 218.2; UL-1795; ANSI Z124.1.2 Our products are listed with: c ETL us

IMPORTANT: Dimensions of fixtures are nominal, may vary and are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.



37.9