

The Safety Tubs 52" x 30" Gelcoat walk-in bath provides a similar bathing experience to larger models but fits in smaller spaces and uses less water. The included tub extender allows this tub to retrofit in the same space as a standard bathtub. The full sized, contoured door with a low door threshold allows ease of entry and exit.

Fully equipped, the Premium Series-available only at Menard's offers all the latest in safety and comfort features with the most advanced therapeutic options and backed by lifetime warranty on the door seal, a 10 year warranty on the tub shell and a 5 year warranty on all other components.

Jet Massage



A soothing and invigorating water jet massage system, the Jet Massage features an in-line heater, an automatic tub cleaning system and Legs-Only massage. Customize back and leg muscle therapies with 13 different water jets. The Jet Massage is combined with all of the features of the Soaker Tub providing an enhanced therapeutic bathing experience.

Air Massage



Experience a soft and caressing all-over body massage powered by a variable speed heated blower that releases thousands of air bubbles rising throughout the water from 26 different air jets. The automatic purge cycle helps keep the system running efficient and clean. The Air Spa is combined with all of the features of the Soaker Tub providing an enhanced therapeutic bathing experience.

Dual Massage System





Combines all of the features of the Soaker Tub, the Air Massage and the Jet Massage Systems for the ultimate therapeutic bathing experience.

Minute Drain® System



Spend less time waiting with this patented innovation, that requires no additional plumbing, once activated it rapidly pumps the water out from within the tub-making it safe to open the door and exit the tub. Included in all systems.

SSM5230 PREMIUM SERIES 52" X 30" WALK-IN BATH

SSM5230XS-XX Soaking Tub

- Tub Extender Kit to fill 60" space
- Available in White or Biscuit and in Left Hand or Right Hand Door/Drain Configuration
- Watertight door system with a lifetime warranty on the door seal
- Built-in chair height seat
- · Color matched trim and cable driven waste and overflow
- Built-in safety bar and textured tub floor
- Cushioned neck rest
- Patented Minute Drain® fast water removal system
- · Premium fast-fill tub faucet and handheld showering wand

SSM5230XJ-XX Jet Massage System Combines all of the features of the Soaking Tub, plus:

- 13 massage jets with variable flow
- Legs-only massage
- · Whirlpool in-line heater
- · Self-cleaning sanitation system

SSM5230XA-XX Air Spa System

Combines all of the features of the Soaking Tub, plus:

- 26 seat and floor air injectors
- · Variable speed heated blower
- · Automatic purge cycle


SSM5230XD-XX Dual System


Combines all of the features of the Soaker Tub, the Jet Massage and the Air Massage Systems for the ultimate therapeutic bathing experience, plus:

 Multi-colored light system positioned at the bottom of the bath that creates a peaceful bathing experience



Products with the Arthritis Foundation's Ease of Use[™] Commendation are tested and proven to make daily tasks easier. Learn more at arthritis.org/easeofuse.





GENERAL SPECIFICATIONS FOR SSM5230XX-XX		
WALK-IN BATHTUB		
INSTALLED SIZE	_52 x 30 x 42 ln. (1321 x 762 x 1067mm)	
WEIGHT	138 Lbs. (62 Kg.)	
WEIGHT w/WATER	904 Lbs. (410 Kg.)	
OPERATING GALLON	60 Gal. (227 L.)	
FLOOR LOADING	85 Lbs./Sq. Ft. (408 Kgs/Sq. m.)	
(PROJECTED AREA)		
CUBE (FT ³)	37.9	

CENEDAL CRECIFICATIONS FOR COMESTONY VV

To Be Specified - Required:

□ Drain Configuration: Left (L) or Right (R)□ Color: White (WH) or Biscuit (BC)

Options:

☐ Handshower Glide Bar: 9HSB☐ 24 inch Grab Bar: 9GB-24

Notes: The jetted heater is designed to maintain water temperature during operation. It will not heat cold water to desired bathing temperature. Tub is supported by the frame and five integrated adjustable feet, no additional support required. Refer to installation instructions supplied with tub for additional information. Provide suitable reinforcement to sub floor for all supports.

Our products are in compliance with the following codes: Uniform Plumbing Code UPC*; National Plumbing Code of Canada; International Plumbing Code IPC*

Our products conform to the following standards: ASME A112.19.7, ASME A112.19.15; CSA B45, CSA B45.5; CSA C22.2 No. 218.2; UL-1795; ANSI Z124.1.2 Our products are listed with: c ETL us

IMPORTANT: Dimensions of fixtures are nominal, may vary and are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.

