

CYCLONE® MXi COMMON VENTING KIT

BENEFITS

- Fewer wall penetrations than standard single-unit venting
- Reduced install cost with easy to install non-powered kits
- Flexibility of using PVC or polypropylene vent material

SPECIFICATIONS

- Approved for use with 120, 150, 199, 250, 300, 400 and 500 Cyclone® models
- Approved for side wall (horizontal) vent applications only
- 50 Feet maximum equivalent length of straight pipe common vent and elbows
- Direct vent configuration only

- Maximum of two water heaters can be common vented
- One kit per water heater required, chose from PVC or polypropylene, model input size
- Kits include backflow preventer plus intake and exhaust adapters. Piping and termination field supplied.
- Each wall penetration requires a 7" hole through the structure
- Common vent kits are UL listed





COMMON VENT KITS (ONE KIT PER WATER HEATER REQUIRED)

Kit	Description
9009152005	PVC Common Vent Kit, 120 – 250 Models
9009227005	PVC Common Vent Kit, 300 – 500 Models
9009132005	Polypropylene Common Vent Kit, 120 -250 Models
9009226005	Polypropylene Common Vent Kit, 300 - 500 Models

Installations must comply with all national, state and local codes.
See kit instructions and corresponding water heater manual for detailed installation instructions and additional information.

For Technical Information call 800-527-1953. A. O. Smith Corporation reserves the right to make product changes or improvements without prior notice.