Residential Combi 1" and Combi 2" Series Water Heaters

Bradford White's Combination Series water heaters are available in both atmospheric and power vented models, perfect for space heating and domestic hot water.



- Provides Domestic Hot Water and Space Heating in One System
- Heat Exchanger Single
 Wall and Double Wall Models
 Available
- Low Heat Exchanger Head Loss
- Hydrojet® Total Performance System Reduces Sediment Buildup
- Vitraglas[®] Lining Provides
 Superior Tank Protection
- Bradford White ICON System[™]
 Intelligent Gas Control
- Available in Atmospheric and Power Vent Models for Increased Installation Flexibility



Combi models are perfect in applications that require supplemental heating as well as installations that utilize fan coils, space heaters, and radiant panels.



Combi1[™] Single Wall **Atmospheric Vent Models**

Model Number	Gallon Capacity	Input BTU/Hr.	GPH Recovery 90°F Rise	Height In.	Diameter In.
C-SW2-504T10FBN	45	65,000	70	59 ¹ / ₄	22
C-SW2-75T10BN	72	76,000	81	621/4	26

- Water Connections 3/4" NPT Factory-Installed True Dielectric Fittings.
- 1" Front NPT Supply and Return Connections.
- 2" Non-CFC Foam Insulation.



Combi1[™] Single Wall **Power Vent Models**

Model Number	Gallon Capacity	Input BTU/Hr.	GPH Recovery 90°F Rise	Height In.	Diameter In.
C-SW2-TW50T10FB	N 45	67,000	72	65 ⁷ /8	22
C-SW2-TW75T10BN	l 72	76,000	82	68 ³ /8	26

- Water Connections 3/4" NPT Factory-Installed True Dielectric Fittings.
- 1" Front NPT Supply and Return Connections.
- 2" Non-CFC Foam Insulation.



Combi2™ Double Wall **Atmospheric Vent Models**

Model Number	Gallon Capacity	Input BTU/Hr.	GPH Recovery 90°F Rise	Height In.	Diameter In.
C-DW2-504T10FBN	45	65,000	70	59 ¹ / ₄	22
C-DW2-75T10BN	72	76,000	81	621/4	26

- Water Connections 3/4" NPT Factory-Installed True Dielectric Fittings.
- 3/4" Front NPT Supply and Return Connections.
- 2" Non-CFC Foam Insulation.



Combi2™ Double Wall **Power Vent Models**

Model Number	Gallon Capacity	Input BTU/Hr.	GPH Recovery 90°F Rise	Height In.	Diameter In.
C-DW2-TW50T10	FBN 45	67,000	72	65 ⁷ /8	22
C-DW2-TW75T10	BN 72	76,000	82	68 ³ /8	26

- Water Connections 3/4" NPT Factory-Installed True Dielectric Fittings.
- 3/4" Front NPT Supply and Return Connections.
- 2" Non-CFC Foam Insulation.







Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Product availability may vary by region.







ATER HEATERS www.bradfordwhite.com