

ElectriFLEX LD™ Commercial Electric Water Heaters

Bradford White's space saving ElectriFLEX LD™ (Light Duty) Commercial Electric Water Heaters offer superior flexibility with multiple conversion options.



- Save time and money with ElectriFLEX LD™ models that are ETL Certified for Quick Supply House or Field Conversion to your requirements
- Maximum Flexibility with 16 different wattages (1.5kW - 12kW*) and factory set voltages that are convertible to or from 120V, 208V, 240V, 277V and 480V
- No kit required for conversion from Three Phase to Single Phase or from Non-Simultaneous to Simultaneous operation saving the installer time
- Voltage and kW input conversion kits allow a maximum number of configurations
- Perfect for multiple applications including Strip Malls, Gas Stations, Fast Food Restaurants, and more

*Dual element models only. Single element models have ten inputs available from 1.5 kW – 6 kW. LE16U and LE112T have four inputs available from 1.5 kW – 3kW.

**Committed to American Manufacturing,
Wholesale Distribution, and Professional Installation.**

BRADFORD WHITE®
WATER HEATERS
www.bradfordwhite.com

With Bradford White's Upright, Utility, Lowboy, and Wall Hung ElectriFLEX LD™ (Light Duty) Commercial Electric models, you'll find a configuration to fit just about anywhere.

ElectriFLEX LD™ Specifications

Upright Models

Model Number	Capacity U.S. Gal.	Recovery at 100°F Rise U.S. GPH	Floor to Top of Heater in.	Jacket Dia. in.	Approx. Shipping Weight lbs.
LE230S3-3	30	18	46 ⁷ / ₈	18	85
LE240S3-3	40	18	46 ⁷ / ₈	20	103
LE250S3-3	50	18	46 ¹ / ₂	22	130
LE265T3-3	65	18	59 ¹ / ₄	22	156
LE280T3-3	80	18	59 ¹ / ₄	24	183
LE2120T3-3	119	18	62 ³ / ₄	28	305

Lowboy Models

Model Number	Capacity U.S. Gal.	Recovery at 100°F Rise U.S. GPH	Floor to Top of Heater in.	Jacket Dia. in.	Approx. Shipping Weight lbs.
LE120L3-3	19	18	24 ³ / ₄	18	58
LE130L3-3*	30	18	29 ³ / ₄	20	86
LE140L3-3*	40	18	31 ¹ / ₄	22	115
LE150L3-3*	47	18	31 ³ / ₄	24	140

Utility Models

Model Number	Capacity U.S. Gal.	Recovery at 100°F Rise U.S. GPH	Floor to Top of Heater in.	Jacket Dia. in.	Approx. Shipping Weight lbs.
LE16U3-1	6	6	16 ¹ / ₂	14	33
LE110U3-1	10	6	17 ¹ / ₂	16	48
LE112T3-1	12	6	27 ³ / ₄	14	48
LE115U3-1	15	6	20 ¹ / ₄	18	55
LE120U3-1	19	6	24 ³ / ₄	18	59

Wall Hung Models

Model Number	Capacity U.S. Gal.	Recovery at 100°F Rise U.S. GPH	Floor to Top of Heater in.	Jacket Dia. in.	Approx. Shipping Weight lbs.
LE16WV3-1	6	6	15 ³ / ₄	14	33
LE112WV3-1	12	6	16 ³ / ₈	18	48
LE120WV3-1	19	6	24 ³ / ₈	18	59

Note: For additional voltage and wattage availability for all models please reference specification sheet or consult factory.

These models are not recommended for sanitation purposes.

* This Lowboy model is provided with an additional insulation blanket.



Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

FEATURES FOR THE SUPPLIER AND INSTALLER:

- Numerous configurations using the conversion kits
- Minimize warehouse space required for storage
- Reduces dollars tied up in inventory
- One model can solve multiple application requirements
- Conversion kits can be shipped FED EX or UPS
- Easy conversion of voltage, phase, and kW input

All models can be easily converted by a qualified installer at the supply house or in the field.



Need to compare a competitive model?
Download our Cross Reference app!
You can also use the RightSpec® Cross Reference guide at www.bradfordwhite.com.



Built to be the Best™ | 800.523.2931

©2015, Bradford White Corporation. All rights reserved.

EFLEXLD-SS 0316

BRADFORD WHITE®
WATER HEATERS
www.bradfordwhite.com