

Electric Brute™ Series

Commercial Electric Water Heaters

Large Volume Bradford White Electric Brute™ Series water heaters are the commercial electric solution to the largest demands for hot water.



- Available in capacities from 150 to 2,500 gallons, inputs from 12kW to 360kW, and voltages from 208v to 600v, Electric Brute™ models provide multiple options for high demand applications
- Low Watt Density INCOLOY® elements are standard because they resist the effects of prolonged high operating temperatures, hard water, acids, corrosion, and thermal shock
- Magnetic Contactors with Immersion Thermostats, 120 volt control circuit with built in transformer, and thermostatically controlled elements in 54kW (max) increments
- Vitraglas® tank lining is an exclusively engineered enamel formula that is applied to the inside of the tank to provide superior protection from the highly corrosive effects of hot water

Committed to American Manufacturing,
Wholesale Distribution, and Professional Installation.



With a 150 psi rating, lifting lugs, and much more as standard equipment, Electric Brute™ water heaters are the choice for commercial and industrial applications where energy savings, high recovery, and extreme hot water output are required.



Standard Features:

- 150 PSI ASME Code Glass-Lined Tank
- Lifting Lugs
- INCOLOY® Heating Elements
- Internal Fusing (above 120 amps)
- Enamel Finished Steel Jacket
- Immersion Thermostats
- Magnetic Contactors
- Terminal Block Connections
- Manual Reset High Limit
- Hinged Door with Keyed Lock
- Magnesium Anode Rods
- ASME Temperature and Pressure Relief Valve
- Channel Iron Skid Base (all models)
- Painted Jacket for Maximum Protection
- 2" Non-CFC Foam Insulation
- Hand Hole Cleanout
- Intertek listed
- Approved for 180°F (82.2°C) Operation
- 3-Year Limited Warranty
- UL-1453 certified

★ ★ Proudly Made in Michigan ★ ★

Electric Brute™ Series Models

Meets or exceed ASHRAE 90.1b (current standard)

Model Number	Gallon Cap. *	Maximum kW	Height In.	Diameter In.	Approx. Shipping Weight lbs.
VR-150-(kW)	150	90	65½	32	650
VR-200-(kW)	200	162	78	32	750
VR-250-(kW)	250	162	92	34	1165
VR-300-(kW)	300	162	80	40	1350
VR-400-(kW)	400	162	80	46	1590
VR-500-(kW)	500	162	92	46	1700
VR-600-(kW)	600	216	92	52	2010
VR-800-(kW)	800	270	104	52	2450
VR-1000-(kW)	1000	360	128	52	3160
VR-1250-(kW)	1250	360	133	58	3792
VR-1500-(kW)	1500	360	129	64	4550
VR-2000-(kW)	2000	360	141	70	5460
VR-2500-(kW)	2500	360	147	76	6553

Note: Electric Brute™ Series models above 90kW at 208V, 240V or 380V, and 162kW at 400V, 415V or 480V, exceed the capacity of a single control panel and may require multiple control panels. Consult the factory for specific details and optional construction.



Optional Features:

- BMS Contacts
- Low Water Cut Off
- Pilot Lights and Manual Limiting Switches
- Powered Anode Rods
- Electronic Step Controller (36 kW & higher)
- Alarm Bell
- Shunt Trip Disconnect
- Low/High Pressure Switch
- Time Clock with Digital Display
- Safety Door Interlock
- Temperature and Pressure Gauges
- Manway



Need to compare a competitive model?

Download our Cross Reference app! You can also use the RightSpec® Cross Reference guide at www.bradfordwhite.com.



Built to be the Best™ | 800.523.2931

©2016, Bradford White Corporation. All rights reserved.

EBS-SS 0916

BRADFORD WHITE
WATER HEATERS
www.bradfordwhite.com