

Job Name:

Engineer/Architect:

Job Location:

Wholesaler:

Submittal Date:

Contractor:

210 Series Pipe Locknut

Use: For use with water, grease, fuels, LP and natural gas, refrigeration, instrumentation, and hydraulic systems in low and medium pressure pipe line connections. Use in combination with brass, copper, and iron pipe.

Design Features:

- Available in a broad range of sizes

Operating Specifications:

Temperature: -65° to +250° F

Working Pressure: Up to 1200 PSI

Vibration: Fair resistance to vibration and pipe movement depending on conditions



FITTING MATERIAL SPECIFICATIONS

Body	Brass
-------------	-------

PART DIMENSIONS (Inches)

Model	DIM. A	HEX. B
210-2	.18	11/16
210-4	.25	7/8
210-6	.25	1"
210-8	.25	1-1/8
210-12	.25	1-1/8

Part Listing:

- | | |
|-----------------------------------|------------------------|
| ☐ 210-2 | 1/8" NPSM thread |
| ☐ 210-4 | 1/4" NPSM thread |
| ☐ 210-4 B | 1/4" NPSM thread, bulk |
| ☐ 210-6 | 3/8" NPSM thread |
| ☐ 210-6 B | 3/8" NPSM thread, bulk |
| ☐ 210-8 | 1/2" NPSM thread |
| ☐ 210-8 B | 1/2" NPSM thread, bulk |
| ☐ 210-12 B | 3/4" NPSM thread, bulk |

