
PEERLESS

8"

(203 mm) 10" (254 mm) 6 1/2"

(165 mm)

P188201LF



KITCHEN FAUCET

■ Single Handle Deck Mount

3 X 1 5/16"~1 1/2" (33~38 mm)

Hole Size

■ 1 or 3 Hole Sink Applications

STANDARD SPECIFICATIONS:

- Single handle kitchen faucets for exposed mounting on 1 or 3 hole sinks with 8" centers.
- 8 7/8" (225mm) long spout swings 360°.
- 1/2"-14 NPSM threaded male inlet shanks.
- Replaceable rotating ball valve with replaceable nonmetallic inlet seats.
- Maximum flow rate 1.8 gpm @ 60 PSI.

8 7/8" (225 mm) Min. 2 1/2" (64 mm) Clearance to Back Splash 360° swing spout Recommended 7 1/2" (190 mm) (102 mm) 1 5/16"~1 1/2" (33~38 mm) Hole Size 1 7/8" (47 mm) Max. Desk Thickness 1/2"-14 NPSM

WARRANTY

 Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.



COMPLIES WITH:

ASME A112.18.1 / CSA B125.1

Indicates compliance to ICC / ANSI A117.1

Verified compliant with 0.25% weighted average Pb content regulations.

1 7/16"

(36 mm) Max. Desk Thickness