

Submitted Model No.:______ Specific Features:

5" to 8" Centers (127 mm - 203 mm) 1/4" (32 mm) Max. Deck Thickness 2" ←(51 mm) Dia. 1 1/8" (29 mm) 0 1 1/8" (29 mm) l⊚ſ 11/16" (17 mm) 12" (305 mm) Long Hose 1/2" (13 mm) Max. Thickness 18 (457 mm) Max. 24" (610 mm) 1/2"-14 NPSM (female) 3/8" or 1/2" bullnose riser Long Hose 1 5/8" (42 mm) 2 1/4" (57 mm) to 2 3/8" -(61 mm) 2 1/8" (54 mm) Dia. 7/16' 0"-1" (0 mm-25 mm) 3 3/8" (86 mm) 1 3/8 (35 mm) Dia. 4 1/2" (107 mm) -(32 mm) Dia.

▲ Designate proper finish suffix

BRIZO

BIDET FAUCET

- Sotria[™] Bath Collection
- Two Handle Bidet Faucet
- 4 Hole Applications
- 5" to 8" Centers
- Diverter with Integral Vacuum Breaker

STANDARD SPECIFICATIONS:

- Three handle bidet faucet for exposed mounting on 4 hole applications.
- Widespread 5" to 8" centers.
- Control mechanism shall be of the rotating ceramic cylinder type with 90° (1/4 turn) rotation.
- Metal drain has pop-up type fitting with plated flange and stopper.
- Diverter with integral vacuum breaker.
- Directional handle for rim flush or rosette spray douche.
- Handles attach to end valves by use of rare earth magnets inside handles.
 No set screw required. Simplifies installation and provides flush mount installation.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ANSI/ASME A112.18.1 / CSA B125.1
- ANSI/ASME A112.18.2 / CSA B125.2

Indicates compliance to ICC/ANSI A117.1

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability.