

Product Type

Wall Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet with Pail Hook

Features & Specifications

- 8" Fixed Centers
- 3" Cross Handles
- Slow Compression Operating Cartridges
- 1/2" NPT Female Thread Inlets
- 3/4" Male Hose Thread Outlet
- Atmospheric Vacuum Breaker, Not Intended for Continuous Pressure Applications
- 8" Center to Center Integral Cast Vacuum Breaker Spout with Pail Hook and Wall Brace
- Atmospheric Vacuum Breaker, Not Intended for Continuous Pressure Applications

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ASSE 1001

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



Manual Sink Faucets



Technical drawings of the fire extinguisher assembly, including a top view and a side view with dimensions in inches and millimeters.

Top View Dimensions:

- Overall width: $3 \pm 1/2$ [76 ± 13]
- Top horizontal distance: $1 - 1/8$ [29]
- Right side diameter: $\varnothing 1 - 3/8$ [35]
- Bottom vertical distance: $1/2$ IPS NIPPLE SUPPLIED BY OTHERS

Side View Dimensions:

- Top horizontal distance: $1 - 7/8$ [48]
- Top horizontal distance: $1 - 1/4 - 2 - 5/8$ [32-67] OVAL FLANGE
- Left vertical distance: $1/2$ NPT PLUG
- Left vertical distance: $3 - 1/8$ [79]
- Left horizontal distance: 4 [102]
- Left horizontal distance: 8 [203]
- Right vertical distance: $9 - 7/8$ [251]
- Right vertical distance: $1 - 1/4$ [32]
- Right vertical distance: $2 - 1/8$ [54]
- Right horizontal distance: $2 - 1/4$ [57]
- Right horizontal distance: $3/4$ A.N. HOSE THREAD OUTLET
- Right horizontal distance: 8 [203]
- Right horizontal distance: $1/4$ [6]
- Right horizontal distance: $\varnothing 2 - 3/4$ [70] FLANGE
- Right horizontal distance: 2 [51]
- Right horizontal distance: $2 - 1/4$ [57]
- Right horizontal distance: $1/2$ NPT FEMALE INLETS
- Right horizontal distance: $1 - 1/4 - 2 - 5/8$ [32-67] OVAL FLANGE
- Right horizontal distance: $1 - 7/8$ [48]
- Right horizontal distance: $1 - 1/8$ [29]
- Right horizontal distance: $\varnothing 1 - 3/8$ [35]
- Right horizontal distance: $1/2$ IPS NIPPLE SUPPLIED BY OTHERS
- Right horizontal distance: $3 - 1/8$ [79]
- Right horizontal distance: 4 [102]
- Right horizontal distance: 8 [203]
- Right horizontal distance: $1 - 1/4 - 2 - 5/8$ [32-67] OVAL FLANGE
- Right horizontal distance: $1 - 7/8$ [48]
- Right horizontal distance: $1 - 1/8$ [29]
- Right horizontal distance: $\varnothing 1 - 3/8$ [35]
- Right horizontal distance: $1/2$ IPS NIPPLE SUPPLIED BY OTHERS

Last Revision: 02/15/2016 • Date Printed: 09/23/2019 • Product specifications subject to change without notice