

Product Type

Deck Mounted Fully Adjustable, 6" - 26" Concealed Hot and Cold Metering Water Sink Faucet

Features & Specifications

- Fully Adjustable, 6" - 26"
- 5-1/4" Rigid / Swing Gooseneck Spout
- 2.0 GPM (7.6 L/min) Spray
- 1-3/4" Vandal Proof MVP Metering Push Handles
- MVP Metering Adjustable Cycle Time Closure Cartridges
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser
- ECAST® design provides durable construction with total lead content equal to or less than 0.25% by weighted average

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown

☐ Submitted with Variations

Date _____



ECAST

ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.

Manual Sink Faucets



Technical drawing of the 100 Series Fire Department Connection (FDC) showing front, side, and top views with dimensions in inches and millimeters.

Front View Dimensions:

- Top nut height: 2-5/8 [67]
- Top nut diameter: $\varnothing 1-1/4$ [32]
- Top nut to coupling nut distance: 4-12 [102-305]
- Top nut to coupling nut distance (overall): 8-24 [203-610]
- Coupling nut diameter: $\varnothing 2-1/4$ [57]
- Coupling nut to riser distance: $\varnothing 1$ [25]
- Coupling nut to riser distance (overall): 3-7/8 [98]
- Coupling nut to riser distance (overall): 2-3/8 [60]

Side View Dimensions:

- Top nut height: 5-3/8 [137]
- Top nut to riser distance: 6-1/2 [165]
- Top nut to riser distance (overall): 11-5/8 [295]
- Top nut to riser distance (overall): 4-1/8 [105]

Top View Dimensions:

- Top nut to riser distance: 1-3/8 [35] MAXIMUM WARE THICKNESS

Other Dimensions:

- Top nut to riser distance: 3°
- Top nut to riser distance: 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER

Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.

