



PLAN
63" [1600mm] Barrier-Free Shower
w/ 3/4" [19mm] Threshold

CENTER DRAIN

PRODUCT SPECIFICATIONS:

- Special installation instruction for this unit must be followed carefully.
- Product complies with NAHB, HUD UM-73A, and CSA B45.5-17/ IAPMO Z124-2017.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- When properly accessorized and installed, product will meet requirements of ADA (2010 Std), ICC/ANSI A117.1-2017, ABA or UFAS.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Integral 1" [25mm] floor nailing flange.
- Shower Area: W- 60" [1524mm] x D- 31-1/4" [794mm]
- Door Opening: W- 60" [1524mm] x H- 75-3/4" [1924mm]
- All dimensions =/ - 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.

6333BF34

63" [1600mm] Barrier-Free Shower w/ 3/4" [19mm] Threshold & Center Drain

Clarion
BATHWARE
44 Amsler Ave.
Shippensburg, PA 16254

Phone: (814) 226-5374
Toll Free: (800) 576-9228
Fax: (814) 226-0730
www.clarionbathware.com

Signatures For Approval:

Date:

Customer: _____
Arch./Engr: _____

DWG. #
6333BF34 -CUT

Quote #: _____
Job Name: _____

By: NMH
Date: 1/2/2018

IMPORTANT NOTICE

Clarion bathware reserves the right to change the design and/or dimensions of its products at any time. This drawing may have been updated since this publication was issued. Before placing an order for any product, refer to our website at www.clarionbathware.com to obtain the most current drawings for any products that you wish to purchase. Compare the date of revision of the drawing that you have with the one on the drawing on our website. If you do not have internet access, please call your sales representative or Clarion Bathware's sales department at 1-800-576-9228.