


ELEVATION



60" [1524mm] Tiled Tub/Shower w/ Molded Shelving

Left Hand Version (8042LSDX) Shown

PRODUCT SPECIFICATIONS:

- Product material AcrylixTM surface with fiberglass composite reinforcement.
- Product complies with NAHB, HUD UM-73A, and CSA B45.5-17/ IAPMO 7.124-2017.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- When properly accessorized and installed, product meets requirements of ADA (2010 Std), ICC/ANSI A117.1-2017, ABA or UFAS.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- Sufficient drain clearance to accommodate above the floor plumbing.
- Reinforced & slip resistant floor.
- Spacious bathing well with molded arm rests.
- Simulated tile walls with molded shelving.
- Integral 1" [25mm] nailing flange.
- Factory drilled 2 1/2" [64mm] overflow.
- Door Opening: W-56" [1422mm] x H-56 1/2" [1435mm]
- Bathwell Dimensions (At Top): W-53 1/2" [1359mm] x D-25" [635mm] x H-13 1/2" [343mm]
- Bathwell Dimensions (At Bottom): W-44" [1118mm] x D-20" [508mm]
- Bathwell Capacity (At Overflow): 48 Gal [182L]
- Water Level (At Overflow): 10" [254mm]
- All dimensions +/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.

8042LSDX or RSDX

60" [1524mm] Tiled Tub/Shower w/18" [457mm] Apron, Molded Soap dish, Molded Soap Ledge, Molded Arm Rests & Left or Right Hand Drain

Clavon
BATHWARE
44 Amsler Ave.
Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730

www.clarionbathware.com

 Signatures For Approval:
 Date:
 Dwg. #

 Customer:
 8042LSDX or RSDX

 Arch./Engr:
 -CUT

 Quote #:
 Dwg. By: NMH

 Job Name:
 DATE: 1/03/2018