





63" [1600mm] Tiled Barrier-Free Shower w/ 3/4" [19mm] Threshold

REAR CENTER DRAIN

## PRODUCT SPECIFICATIONS:

- Product material Acrylix<sup>TM</sup> surface with fiberglass composite reinforcement.
- Special installation instructions for this unit must be followed carefully.
- Product complies with NAHB, HUD UM-73A, and CSA B45.5-17/ IAPMO Z124-2017.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- When properly accessorized and installed, product meets requirements of ADA (2010 Std), ICC/ANSI A117.1-2017, ABA or UFAS.
- Simulated tile walls with ribbon design.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Integral 1" [25mm] floor nailing flange.
- Shower Floor: W- 60" [1524mm] x D- 31-1/4" [794mm]
- All dimensions +/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.

## 8333BF34

63" [1600mm] Barrier-Free Shower w/ 3/4" [19mm] Threshold & Rear Center Drain

| Clar        | ion   |
|-------------|-------|
| ВАТ         | HWARE |
| 44 Amsler A | Ave.  |

Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com 
 Signatures For Approval:
 Date:
 Dwg. #

 Customer:
 8333BF34-CUT

 Arch./Engr:
 Dwg. By: NMH

 Job Name:
 DATE: 11/22/2017

\*\*\* IMPORTANT NOTICE \*\*\*