



40" [1016mm] Simulated Tile Barrier-Free Shower w/3/4" [19mm] Threshold

REAR CENTER DRAIN

## PRODUCT SPECIFICATIONS:

- \* Special installation instructions for this unit must be followed carefully.
- \* Product complies with NAHB, HUD UM-73A, and ANSI-Z124.1.2.
- \* Product has a Class B fire rating as determined by ASTM E-84 test method.
- When properly accessorized and installed, product meets requirements of ADA (2010 Std), ICC/ANSI A 117.1-2009, ABA or UFAS.
- Reinforced & slip resistant floor.
- \* Integral 1" [25mm] nailing flange.
- \* Integral 1" [25mm] floor nailing flange.
- Shower Floor: W-36" [914mm] D-36" [914mm]

- Accepts Clarion Bathware Model #IN89 Dome.
- All dimensions +/- 1/2" [12.8mm]
- \* Clarion Bathware reserves the right to change design and/or dimensions.
- \* Dimensions are the same for RE, MP, and all other versions of this model.

## 8940BF34

40" [1016mm] Simulated Tile Barrier-Free Shower w/ 3/4" [19mm] Threshold & Rear Center Drain

Clarion
BATHWARE
44 Amsler Ave.
Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com

Signatures For Approval: Customer: Arch./Engr:	Date:	Dwg. # 8940BF34-CUT
Quote #:		Dwg. By: NMH