



SIDE VIEW

TOP VIEW



CROSS SECTION OF THRESHOLD



SUBMITTAL

This shower enclosure shall be model SST 6334 BF .75 right, or left. Finished surface shall be of a sanitary grade solid surface exhibiting a minimal thickness of 55 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 63" x 34" x 78 3/4".

The unit shall meet ANSI Z124.1-2, ANSI A117.1, ADA, HUD, BOCA, NAHB UPC, and shall meet the requirements of the Southern Building Code.

The enclosure shall be equipped with the following accessories:

- 1) One 36" x 1 1/2" diameter 18 gauge stainless steel grab bar on the back wall, 2) one 24" x 1 1/2" 18 gauge stainless steel grab bar on the side wall, both with 1 1/2" statute clearance, secured from the rear with stainless steel bolts and 3" x 3" x 11 gauge metal mounting plates, 3) 26" x 21" frameless wood grain phenolic fold up seat, 4) molded corner soap ledges, 5) one inch diameter, 18 gauge stainless steel curtain rod with receiver cups, 6) tri cell cell backing, 7) leg ledge, 8) tile finish, 9) diamond accents, 10) EasyBase™ self sustaining bottom, 11) 3/4" threshold.

OPTIONAL ACCESSORIES:

Factory Plumbing Install Option: ☐ YES ☐ NO

☐ PB Pressure Balancing Mixing Valve (ADA / ANSI)

☐ HH Hand held shower assembly with slide bar, vacuum breaker and 60" hose (ADA / ANSI)

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 63" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSURE.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

| Job Name | Approved By | Name | Date | COMFORT DESIGNS | |
|--|-------------|------|------|--|--------------|
| Project No | Architect | | | Model No. SST 6334 BF .75 L-Bar-I | |
| Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com | Engineer | | | Drawing No. SST 6334 BF .75 HBW HSW WGPB CR VP EB | |
| | Rep | | | Date Issued. 4-4-12 | Drawing Rev. |
| | Wholesaler | | | Material. Solid Surface | |
| | Comments | | | Color. | |
| | | | | Dimensions are in inches. Due to the nature of the materials dimensions may vary $\pm 1/2$ " | |