



SIDE VIEW



CROSS SECTION OF THRESHOLD





SUBMITTAL

This shower enclosure shall be model SSS 3698 BF .625 right, or left. Finished surface shall be of a sanitary grade solid surface exhibiting a minimal thickness of 55 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 39" \times 39 1/2" \times 76 5/8".

The unit shall meet ANSI Z124.1-2. ADA, MAS, HUD, BOCA, NAHB UPC, and shall meet the requirements of the Southern Building Code.

The enclosure shall be equipped with the following accessories: I) One 20" \times 33 I/2 \times I I/4" diameter 18 gauge stainless steel peened L- grab bar, with I I/2" statute clearance, secured from the rear with stainless steel bolts and 3" \times 3" \times 11 gauge metal mounting plates, 2) frameless 32" \times 21" white padded fold up seat, 3) molded corner soap ledges, 4) one inch diameter, 18 gauge stainless steel curtain rod with receiver cups, 5) tri cell backing, 6) EasyBase $^{\text{TM}}$ self sustaining bottom, 7) 5/8" threshold.

OPTIONAL ACCESSORIES:
Factory Plumbing Install Option: YES NO
☐ PB Pressure Balancing Mixing Valve (ADA / MAS)
☐ HH Hand held shower assembly with slide bar, vacuum breaker and 60" hose (ADA / MAS)

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 39" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

Till Larger With Bedding Compound						
Job Name	Approved By	Name	Date	COMFORT DESIGNS		
Project No	Architect			Model No. SSS 3698 BF .625 MAS-I		
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800,443,7269 fax 731,925,4290 www.comfortdesignsbathware.com	Engineer			Drawing No. SSS 3698 BF .625 PLB FPD CR VP EB		
	Rep			Date Issued. 3-28-12	Drawing Rev.	
	Wholesaler			Material. Solid Surface		
	Comments			Color.		
				Dimensions are in inches. Due to the nature of the materials dimensions may vary \pm 1/2"		