



## SIDE VIEW



## CROSS SECTION OF THRESHOLD





## SUBMITTAL

This shower enclosure shall be model XSS 3600 BF .625, right or left. Finished surface shall be of a sanitary grade applied acrylic. The base shall be attached to the sump in such a manner to form an integral part with an inner and outer coating of polyester resin. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of  $39" \times 39$  I/4"  $\times$  77 I/8". The unit shall meet CSA B45.5-II, HUD-UM73, and Home Innovation Research Lab.

## HANDED BY THE VALVE

The enclosure shall be equipped with the following accessories: I) One  $18" \times 33 \text{ I}/2" \times 1 \text{ I}/4"$  diameter white horizontal L-grab bar, 2) One  $24" \times 1 \text{ I}/4"$  diameter white vertical grab bar, both with I I/2" statute clearance, mounted with stainless steel bolts, and secured from the rear with  $3" \times 3" \times 11$  gauge metal mounting plates, 3) Molded seat, 4) One inch diameter, 18 gauge white curtain rod with receiver cups, 5) Molded corner soap ledges, 6) Factory installed Armor Core Easy Base, 7) 5/8" threshold.

NOTE: SIZE AND SHAPE OF THE MOLDED SEAT DOES NOT COMPLY WITH ADA, OR ANSI A1 17.1.

OPTIONAL ACCESSORIES:
Factory Plumbing Install Option: YES NO
PB Pressure Balancing Mixing Valve (ADA / ANSI)
☐ HH Hand held shower assembly with slide bar, vacuum breaker and 60" hose (ADA / ANSI)

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 39" OF OVERALL WIDTH, THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FORA DRYWALL ENCLOSED FIRE WALL INSTALLATION, ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSURE.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

Job Name	Approved By Print Name		Date	COMFORT DESIGNS	
Project No	Approved By Signature			Model No. XSS 3600 BF .625	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269	Architect			Drawing No. XSS 3600 BF .625 WLB WVB MS WCR Easy Base	
	Engineer			Date Issued, 4-3-12	Drawing Rev. 5-11-17
	Rep			Material. Acrylic Surface	
	Wholesaler			Color.	
fax 731.925.4290 www.comfortdesignsbathware.com	Comments		Dimensions are in inches. Due to the nature of the materials dimensions may vary $\pm$ I/2"		