


CROSS SECTION OF THRESHOLD





SUBMITTAL

This shower enclosure shall be model XST 3838 BF .625 right, or left. Finished surface shall be of a sanitary grade polyester gelcoat exhibiting a minimal thickness of 15 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of $38" \times 39" \times 78$ 3/8". The unit shall meet ANSI Z I 24. I-2, ADA, MAS, HUD, BOCA, NAHB UPC, and shall meet the requirements of the Southern Building Code.

The enclosure shall be equipped with the following accessories: I) One 20" \times 33 I/2 \times I I/4" diameter I8 gauge white textured L- grab bar, with I I/2" statute clearance, secured from the rear with stainless steel bolts and 3" \times 3" \times I I gauge metal mounting plates, 2) frameless 32" \times 21" white padded fold up seat, 3) molded corner soap ledges, 4) one inch diameter, I8 gauge

3) molded corner soap ledges, 4) one inch diameter, 18 gauge white curtain rod with receiver cups, 5) tile finish, 6) diamond accents, 7) tri cell backing, 8) EasyBase™ self sustaining bottom, 9) 5/8" threshold.

OPTIONAL ACCESSORIES: Factory Plumbing Install Option: YES NO					
☐ PB Pressure Balancing Mixing Valve (ADA ./ MAS)					
☐ HH Hand held shower assembly with slide bar, vacuum breaker and 60" hose (ADA / MAS)					

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 38" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE, THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSED FIRE WALL ENCLOSURE.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

Job Name	Approved By	Name	Date	COMFORT DESIGNS		
Project No	Architect			Model No. XST 3838 BF .625 MAS-1		
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Engineer			Drawing No. XST 3838 BF .625 WLB FPD WCR VP EB		
	Rep			Date Issued. 3-28-12	Drawing Rev.	
	Wholesaler			Material. Gelcoat		
	Comments			Color.		
				Dimensions are in inches. Due to the nature of the materials dimensions may vary \pm 1/2"		