



SUBMITTAL

This shower enclosure shall be model XSS 6036 BF 2.0" right, or left. Finished surface shall be of a sanitary grade polyester gelcoat exhibiting a minimal thickness of 15 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of $60" \times 36" \times 76"$. The unit shall meet ANSI Z124.1-2. HUD, FHA, BOCA, NAHB UPC, and shall meet the requirements of the Southern Building Code.

SIDE VIEW TOP VIEW 36" 39\frac{3}{4}" \ 34\frac{3}{4}" 32\frac{1}{2}" CROSS SECTION OF THRESHOLD

Steel Stiffener

Gelcoat Surface

Coordinate Finished Floor

Height For Code. -

The enclosure shall be equipped with the following accessories:

I) One 30" \times I 1/4" diameter 18 gauge white grab bar horizontal on the back wall, 2) one 24" \times I 1/4" diameter 18 gauge white grab bar horizontal on the side wall, 3) one 24" \times I 1/4" diameter 18 gauge white grab bar vertical on the seat wall, all with 1 1/2" statute clearance, secured from the rear with stainless steel bolts and 3" \times 3" \times I I gauge metal mounting plates, 4) molded shelf on the back wall, 5) frameless white 28 1/2" \times 21" HDPE fold up seat, 6) one inch diameter, 18 gauge white curtain rod, with receiver cups, 7) tri cell backing, 8) 2.0" threshold.

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 60" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSED.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

(Backt	ill Larger Cutout With Bedd	ing Compound)				
Job Name	Approved By	Name	Date	COMFORT DESIGNS		
Project No	Architect			Model No. XSS 6036 BF 2.0-I		
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269	Engineer			Drawing No. XSS 6036 BF 2.0 WHBW WHSW FHDP WCR		
	Rep			Date Issued. 4-12-12	Drawing Rev.	
	Wholesaler			Material. Gelcoat		
	Comments			Color.		
fax 731.925.4290 www.comfortdesignsbathware.com				Dimensions are in inches. Due to the nature of the materials dimensions may vary \pm 1/2"		

Center of Drain -

Bedding Compound

(By Others)

Drain Core 6" Minimum.