


TOP VIEW 50" 24" 184 50" Slip Resistant Surface





CROSS SECTION OF THRESHOLD





SUBMITTAL

This shower enclosure shall be model SSB 4848 BF I.0 DE base, center drain. Finished surface shall be of a sanitary grade solid surface exhibiting a minimal thickness of 55 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a I5% minimum fiberglass content.

The unit shall have outside dimensions of $50" \times 50" \times 4$ I/2" with a one inch Change Of Level threshold.

The unit shall meet ANSI Z124.1-2, BOCA, UPC, CSA, Home Innovation Research Lab, and shall meet the requirements of the Southern Building Code.

HANDED BY THE DRAIN.

The enclosure shall be equipped with the following features:

- 1) One inch Change Of Level Threshold,
- 2) EasyBase™ self sustaining bottom,
- 3) Slip resistant surface on floor,
- 4) Solid Surface finish,
- 5) Left ot right drain location.

THIS UNIT FEATURES THE OUTSIDE DIMENSIONS OF 50" AND 50". FINISHED WALLS ABOVE THE SHOWER BASE BY OTHERS,

Job Name	Approved By Print Name		Date	COMFORT DESIGNS	
Project No	Approved By Signature			Model No. SSB 4848 BF I.O DE C Base-I	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269	Architect			Drawing No. SSB 4848 BF 1.0 DE C Easy Base	
	Engineer			Date Issued. 6-25-14	Drawing Rev
	Rep			Material Solid Surface	
	Wholesaler			Color.	
fax 731,925,4290 www.comfortdesignsbathware.com				Dimensions are in inches. Due to the nature of the materials dimensions may vary \pm 1/2"	