FRONT VIEW Curtain Rod · Grab Bar Soap Dish Soap Dish L-Shaped Grab Bar $73\frac{3}{4}$ Fold Up Seat 3931 183 -38

SIDE VIEW

comfortdesigns

SUBMITTAL

This shower enclosure shall be model SSS 3838 BF .75 right, or left. Finished surface shall be of a sanitary grade solid surface exhibiting a minimal thickness of 55 dry mils and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.


The unit shall have outside dimensions of $38" \times 38" \times 78"$.

The unit shall meet ANSI Z124.1-2. ANSI A117.1, ADA, HUD, BOCA, NAHB UPC, and shall meet the requirements of the Southern Building Code.

The enclosure shall be equipped with the following accessories: I) One 18" \times 33 1/2 \times 1 1/2" diameter 18 gauge stainless steel L-grab bar, 2) one 24" \times 1 1/2" 18 gauge stainless steel grab bar vertical on the valve wall, both with I I/2" statute clearance, secured from the rear with stainless steel bolts and 3" \times 3" \times 11 gauge metal mounting plates, 3) 32" x 21" frameless wood grain phenolic fold up seat, 4) molded corner soap ledges, 5) one inch . diameter, 18 gauge stainless steel curtain rod with receiver cups, tri cell backing, 7) EasyBase[™] self sustaining bottom,

- 8) 3/4" threshold.

OPTIONAL ACCESSORIES:




Factory Plumbing Install Option: YES NO ☐ PB Pressure Balancing Mixing Valve (ADA / ANSI) HH Hand held shower assembly with slide bar, vacuum breaker and 60" hose (ADA / ÁNSI)

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 38" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE, THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS, THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION, ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSURE.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

CROSS SECTION OF THRESHOLD

Coordinate Finished Floor Height For Code Finished Floor May Be No More Than 1/4" Below The Top Of Compartment Threshold.



Fill Larger with Bedding Compound					
Job Name	Approved By	Name	Date	COMFORT DESIGNS	
Project No	Architect			Model No. SSS 3838 BF .75-l	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Engineer			Drawing No. SSS 3838 BF .75 SLB VSW WGPH CR VP EB	
	Rep			Date Issued. 4-23-12	Drawing Rev.
	Wholesaler			Material Solid Surface	
	Comments			Color.	
				Dimensions are in inches. Due to the nature of the materials dimensions may vary \pm 1/2"	