Sollus ProTrench

Code Compliant & High Performance Professional Trench Drain Shower Bases

Safety

Wall-to-wall patented trench drain for 100% water containment Low 3/4-inch entry threshold One common 2% slope

Innovative Design

Sleek Water Performance Grate Compatible with solid surface walls for seamless look Easy installation- installs directly to slab Code Compliant: 2016 CBC, ADA, TAS, MASS

Durability

High-performing, compression-molded solid surface Impact, stain, chemical, and mold resistant Easy cleaning and maintainability



NEW

00



Sollus ProTrench Code Compliant & High Performance Professional Trench Drain Shower Bases

Compression-Molded Solid Surface ADA Compliant Transfer & Roll-In Shower Bases







Exterior Dimensions 38"W x 37"D x 3 1/2"H Interior Dimensions: 36"W x 36"D x 3/4"H

Code Compliant: 2016 CBC, ADA, TAS, MASS





SWB6234TR.75 Low 3/4" entry threshold

Exterior Dimensions 62"W x 33"D x 3 1/2"H Interior Dimensions 60"W x 32"D x 3/4"H

Code Compliant: 2016 CBC, ADA, TAS, MASS

NEW Innovative Trench Design with **HyperTrench Technology**

High performance, 304 stainless steel water capturing grate design

New quick connect HyperTrench grate clicks into place

Shallow and low ³/₄" threshold allows for easy flooring transitions and sloping floor back to drain

Sollus ProTrench is available in 12 solid surface finishes. Visit comfortdesignsbathware.com for more information.