


Submitted Model No.: \_ Specific Features: \_



## ▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

# BATHROOM FAUCET

- Dorval<sup>™</sup> Collection
- Single Handle Deck Mount

## **FEATURES:**

- Touch<sub>2</sub>O.xt® Technology
- DIAMOND Seal® Technology

#### **STANDARD SPECIFICATIONS:**

- Max. flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- One or three hole mount (escutcheon included)
- · Diamond coated ceramic cartridge
- 1/4" O.D. straight, staggered PEX supply lines
- Optional red/blue indicator provided
- LED indicator light signals on-off, water temperature and when batteries run low
- Uses 6 AA (included) or 6 C (optional) batteries
- Optional 120V AC adapter available (3 prong grounded outlet required)
- Models have drain with metal push pop-up type

## WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



# **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
  ASME A112.18.2 / CSA B125.2
  Indicates compliance to
- 6 ICC/ANSI A117.1
- EPA WaterSense®

**Delta Faucet Company** 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON NSP 4L1 © 2023 Delta Faucet Company