



see what Delta can do<sup>SM</sup>

## BLOWDOWN TEMPERING VALVE

### FEATURES:

- Compliant with drain temperature limitations of plumbing code
- Prevents damage to PVC piping due to overtemperature conditions
- Rugged, clog resistant valve design
- Operates in any orientation
- Modulates to conserve water
- Effluent tempering capacity limited only by cold water flow rate through the valve
- For use with Delta commercial steam generators (5COM)

### STANDARD SPECIFICATIONS:

- Water inlet size is 1/2" NPT
- Drain size is 1" NPT
- Maximum water inlet pressure 125 PSIG (8.6BAR)
- Maximum temperature is 250°F (121°C)
- Full open set temperature 120°F (49°C)
- Closing temperature 110°F (43°C)

### WARRANTY

- Steam Generators – Lifetime limited warranty; or for commercial purchasers (including for steam bath generators with model numbers beginning with 5COM, which are intended solely for heavy commercial use), one (1) year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts for Steam Bath Generators, Controls, Spa Options and Accessories – two (2) years from the date the product is received by the original consumer purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, one (1) year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to [www.deltafaucet.com](http://www.deltafaucet.com) for the complete details of our limited warranty.

