




Submitted Model No.:

Specific Features:







▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-144717 Rev. D



## TUB AND SHOWER **FAUCET TRIM**

- Olmsted<sup>™</sup> Bath Collection
- Tub and Shower

## **STANDARD SPECIFICATIONS:**

- Monitor<sup>®</sup> 14 Series pressure balanced bath mixing valve with Scald-Guard®
- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere
- in the system.

  For use with MultiChoice® Universal rough For use with Multicnoice Universal rough valve body. (R10000 Series).
  Back-to-back installation capability.
  Solid brass forged body.
  Temperature only controlled with handle.
  Field adjustable to limit handle rotation into

- hot water zone.
- 120<sup>o</sup> maximum handle rotation.
- All parts replaceable from the front of the valve.


## **WARRANTY**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

## **COMPLIES WITH:**

ASME A112.18.1 / CSA B125.1

Indicates compliance to Indicates compliance to ICC/ANSI A117.1 - Valve control only





55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, Ontario Canada N5P 4L1 © 2016 Masco Corporation of Indiana