

Submitted Model No.:

Specific Features:

Min. 2 1/2" (64 mm) Clearance to Back Splash — 5 1/8" (130 mm) 9 3/8" (238 mm) 3" (76 mm) 13 5/8" (346 mm) 6 3/8" (162 mm) - 2 5/16" (59 mm) 1 1/4" -(32 mm) min. 1 3/8" (35 mm) Hole Size 8" (203 mm) 33 1/2" (851 mm) 2 1/2" 35" (889 mm) (64 mm) Мах. 3/8" Compression Fittings 14 1/8" (359 mm) 6 7/8" (175 mm) 3x 1 3/8" (35 mm) Hole Size 2 1/2" (64 mm) Max 8" (203 mm) Centers 10 3/4" -(273 mm)

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

\Delta DELTA

KITCHEN FAUCETS

- Izak® Pull-Down Collection
- Single Handle Deck Mount
- 1 or 3 Hole Sink Applications
- Diamond Seal[®] Technology
- Integrated Supply Tubes

STANDARD SPECIFICATIONS:

- Centermount or 8" (203 mm) centers with 10 3/4" (273 mm) escutcheon.
- 13 5/8" (346 mm) high, 9 3/8" (238 mm) long, spout swings 360°
- Lever handle. Control mechanism is the diamond embedded ceramic disc cartridge.
- Touch-Clean[®] 2 function (stream/spray) sprayhead.
 Quick Snap[®] connect hoses.
- Magnetic docking system secures sprayer to spout.
- Pull-down wand operates in an aerated or spray mode via an ergonomic toggle diverter.
- Red/blue graphics on handle button to indicate hot/cold temperature.
- Integral double check valves in sprayer assembly.
- Disposable hose lead to aid installation.
- Mounting wrench to assist in tightening mounting nut securely.
- Hose travels inside mounting shank so it will not interfere
- Keyed escutcheon to help alignment and aid installation.
- 3/8" O.D. straight, staggered PEX supply tubes, 33 1/2" (851 mm) and 35" (889 mm).
- Maximum 1.80 gpm @ 60 psi, 6.8 L/min @ 414 kPa

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.6
- Indicates compliance to ICC/ANSI A117.1
- Verified compliant with .25% weighted average Pb content regulations.



55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2015 Masco Corporation of Indiana