


LAVATORY FAUCETS

- Dryden™ Collection
- Diamond Seal® Technology
- Single Handle Deck Mount
- 1 Hole Mount
- 5" Riser

Submitted Model No.: _____

Specific Features: _____



STANDARD SPECIFICATIONS:

- Single handle lavatory deck faucet.
- 1 hole mount.
- 5 3/8" (137 mm) long spout.
- 1 1/4" minimum - 1 3/4" maximum hole size.
- Lever handle. Control mechanism is the diamond embedded ceramic disc cartridge.
- Control handle shall return to neutral position when valve is turned off.
- 3/8" O.D. straight, staggered pex supply tubes 29" (737 mm) and 30" (762 mm) long.
- Max. 1.50 gpm @ 60 psi, 5.7 L/min @ 414 kPa
- Models include finished 5" riser.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®
- Meets 0.25% weighted average lead content regulations.



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-L-751-DST Rev. B

55 E. 111th Street, Indianapolis, Indiana 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2015 Masco Corporation of Indiana