

DEMD Series Electronic Lavatory Faucets (Infrared)



HDF[®]
COMMERCIAL



HARDWIRE OPERATED WALL MOUNT LAVATORY FAUCET



SIDE VIEW



Note: Measurements may vary ± 6 mm (0.25")

SPECIFICATION: (example)

- Wall mount electronic lavatory faucet
- Sensor detects user's hand to activate water flow
- 24 VAC to 9 VDC converter supplied for use with standard transformer like 060704A (order separately) – 060958A DEMD Power Supply can also be used, but without converter
- 0.5 gpm (1.9 L/min) aerator

DEMD-402 SERIES

- Electronic faucet for cold or pre-mixed water – 8" spout

DEMD-402LF (Chrome)

DEMD-402LF-NS (Nickel Stainless)


DEMD-404 SERIES

- Electronic faucet for cold or pre-mixed water – 6" spout

DEMD-404LF (Chrome)

DEMD-404LF-NS (Nickel Stainless)

FLOW RATE vs PRESSURE



APPROVALS:



- IAPMO certified
- Complies to ASME A112.18.1/CSA B125.1
- Indicates compliance to ICC/ANSI A117.1
- Verified compliant with 0.25% weighted average Pb content regulations

(Contact Delta Representative for State and/or Local Approvals.)

Refer to www.specselect.com for individual models.

Flow Rates are at 60 PSI.
Note: Use this page front and back as a product submittal sheet.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.

DSP-DEMD-400 Rev. I


DEMD Series Electronic Lavatory Faucets (Infrared)

HDF[®]
COMMERCIAL


DELTA

HARDWARE OPERATED WALL MOUNT LAVATORY FAUCET

TYPICAL INSTALLATION – BASIN SINK



TYPICAL INSTALLATION – TROUGH SINK



Note: Measurements may vary ± 6 mm (0.25")

DEMD-402 SERIES

Electronic faucet for cold or pre-mixed water – 8" spout

- DEMD-402LF – Chrome Finish
- DEMD-402LF-NS – Nickel Stainless Finish

DEMD-404 SERIES

Electronic faucet for cold or pre-mixed water – 6" spout

- DEMD-404LF – Chrome Finish
- DEMD-404LF-NS – Nickel Stainless Finish

OPERATION

Sensing Range:

- Factory set to 8.0" \pm 1.5" (200 mm \pm 40 mm)
- Adjustable from 3.15" to 11.8" (80 mm to 300 mm) with optional remote control
- Minimum distance of 12.5" (318 mm) from sensor to sink/trough surface

Maximum Run Time:

- 90 seconds, adjustable with remote control

OPTIONAL ACCESSORIES

(Order Separately)

- 060958A**
 - DEMD Plug-In Power Supply – Output 9 VDC (Optional)
- 060967A**
 - Remote Control (Optional)
- 063256A (Chrome Only)**
 - 0.35 gpm (1.32 L/min) spray outlet
- 060961A (Chrome)**
 - 1.0 gpm (3.8 L/min) aerator
- 061118A (Chrome)**
 - 1.5 gpm (5.7 L/min) Careguard[®] laminar outlet
- 061046A**
 - Battery Box for one 9 volt battery
 - Battery operation requires separate order of Battery Box and 9 volt battery