

▲ Designate proper finish suffix



## LAVATORY FAUCETS

- Windemere<sup>™</sup>Bath Collection
- Two Handle Deck Mount
- 3 Hole Sink Applications
- 4" Centerset

## STANDARD SPECIFICATIONS

- Two handle lavatory faucets for exposed mounting on 3 hole sinks with 4" centers.
- 4" (102 mm) centerset.
- 5 1/8"(130 mm) long. 5 7/8"(149 mm) high spout.
- 1/4 turn handle stops.
- All operating parts shall be replaceable from the top.
- Hot and cold stems are interchangeable.
- 1/2" -14 NPSM threaded male inlet shanks.
- Lever handle control mechanism is a rotating cylinder type with stainless steel plate and 90° rotating, with replaceable non-metallic seats.
- Models include metal pop-up type fitting with plated metal flange and stopper cap.
- Maximum flow rate 1.5 gpm @ 60 PSI.

## WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the Original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all Industrial. Commercial and business applications.










## **COMPLIES WITH**

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

lndicates compliance to ICC / ANSI A117.1

- EPA WaterSense
- CSA Certified

Verified compliant with 0.25% weighted average Pb content regulations.





55 E. 111th Street, Indianapolis, Indiana 46280 395 Matheson Blvd. E., Mississauga, ON L4Z 2H2 © 2010 Masco Corporation of Indiana