

Pacemaker® Single Bowl Hospitality Sink No Faucet Ledge Models BPSFR1215 and BPSFRQ1215

GENERAL

Fine quality sink bowl seamlessly formed of #20 gauge, type 304 (18-8) nickel bearing stainless steel. Top Mount.

DESIGN FEATURES

Bowl Depth: 6-1/8" (156mm)

Coved Corners: 1-3/4" (44mm) vertical and horizontal radius. Rim Height: 3/16" (5mm) below outside ledge of sink.

Finish: Exposed surfaces are hand polished to a Bright

Underside: Fully undercoated to dampen sound and prevent

condensation.

OTHER

Drain Opening: 2" (51mm)

Sink complies with ASME A112.19.3-2008 / CSA B45.4-08.



These sinks are listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code and the National Plumbing Code of Canada.



These sinks are compliant to ADA and ANSI/ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.



Model BPSFR(Q)1215


OPTIONAL ACCESSORIES

Cutting Board: CB912

SINK DIMENSIONS*


	U-Channel Model	Quick-Clip Model	Overall		Inside Bowl			Cutout in Countertop (1-1/2" (38mm) Radius Coners		Minimum Cabinet Size
ı	Number	Number	L	W	L	W	D	L	W	
	BPSFR1215	BPSFRQ1215	12-1/2 (318mm) (15 381mm)	9-1/4 (235mm)	12 (305mm)	6-1/8 (156mm)	11-7/8 (302mm)	14-3/8 (365mm)	18 (457mm)


^{*}Length is left to right. Width is front to back.




In keeping with our policy of continuing product improvement, Elkay r eserves the right to change product specifications without notice.

Installation Profile







This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked