

## **GENERAL**

High quality single bowl sink is formed of #20

(1.0mm) gauge, type 304 (18-8) nickel bearing stainless steel.

Top Mount

## **DESIGN FEATURES**

Bowl Depth: 7-1/2" (191mm).

Coved Corners: 3" (76mm) vertical radius.

Bowl and Faucet Deck Recess: 1/2" (13mm) total recess below rim provides protection against water overflowing onto countertop 1/8" (3mm) recess for styled faucet deck configuration and 3/8" (10mm) for the extra deep drop ledge providing additional faucet spout clearance.

Finish: Exposed surfaces are machine polished to a Brushed Satin

finish

Underside: Fully undercoated to prevent condensation and

reduce sound.

## **OTHER**

Drain Opening: 3-1/2" (89mm)

Sink complies with ASME A112.19.3/ CSA B45.4

UPC ®

Sinks are listed by IAPMO® as meeting the applicable requirements of the Uniform Plumbing Code®, International Plumbing Code®, and National Plumbing Code of Canada.

## **OPTIONAL ACCESSORIES**


Rinsing Baskets: LKWRB2115SS, LKERBSS and LKWUCSS

Cutting Boards: CB1516
Bottom Grid: LKWBG2115SS
SINK DIMENSIONS (INCHES)\*

Model Number	Overall		Inside Each Bowl			Cutout in Countertop [1 <sup>1</sup> / <sub>2</sub> " (38mm) Radius Corners]		No. of 1 <sup>1</sup> / <sub>2</sub> " (38mm) Dia. Faucet Holes 4" (102mm)	Minimum Cabinet
	L	W	L	W	D	L	W	Centers	Size
ECC2522	25 (635mm)	22 (559mm)	21 (533mm)	15¾ (400mm)	7½ (191mm)	24% (619mm)	21% (543mm)	1, 2, 3 or 4	30

<sup>\*</sup> Length is left to right. Width is front to back.





Model ECC25224 Illustrated

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice.


This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

2222 Camden Court Oak Brook, IL 60523

**Elkay** www.elkay.com

www.elkaypro.com

©2014 Elkay



Model ECC25224

<sup>\*\*</sup> Template 0000001188 - Available for download at elkay.com, elkaypro.com or by contacting customer service.