

# LADYLUX3 CAFÉ TOUCH

## Pull-Down kitchen faucet with touch technology

MODEL # 30226

GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172  
Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | [us-customerservice@grohe.com](mailto:us-customerservice@grohe.com)

*Pure Freude an Wasser*



**ADA**

### Product Description:

Pull-Down kitchen faucet with touch technology

### Standard Specification:

with Grohtherm Micro

- GROHE SilkMove® ceramic cartridge
  - GROHE StarLight® finish
  - GROHE SuperSteel Infinity Finish™
  - Single hole installation
  - **Touch: activation of cold water via skin contact**
  - 6 V lithium-battery supply (type CR-P2)
  - **CE approved**
  - Indication of battery status through different pulses of water
  - Safety shut down circuit (when battery nearly empty)
  - **Solenoid valve**
  - Automatic safety stop after 60 sec.(factory set)
  - Type of protection IP 44
  - **SpeedClean** anti-lime system
  - Swivel Spout
  - Swivel area 360°
  - Adjustable flow rate limiter
  - **Pull-out locking dual spray control - switches back and forth between regular flow and spray**
  - Automatic returning
  - Integrated non-return valve
  - Locking Push Button Control - to switch from regular flow to spray
  - Automatic return to aerator
  - Stainless Steel Braided Flexible Supplies
  - Quick installation system
  - **Protected against backflow**
  - **Grohtherm Micro 34 507 000**
  - **thermostatic scalding protection**
  - GROHE TurboStat® thermoelement
  - GROHE StarLight® finish
  - Built-in non-return valve
  - Dirt strainers
- including connection set
- Max. pressure differential 5:1
  - Min. recommended pressure 15 psi

### Applicable Codes & Standards:

*Pure Freude an Wasser*



GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172  
Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | [us-customerservice@grohe.com](mailto:us-customerservice@grohe.com)

- Energy Policy Act of 1992
- NSF 61
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations
- ICC/ANSI A117.1

**Color:**

- ☐ 30226 000 chrome
- ☐ 30226 DC0 supersteel