GROHE BLUE CHILLED & SPARKLING Starter kit MODEL # 31251DC2











Product Description: GROHE BLUE CHILLED & SPARKLING Starter kit

Standard Specification:

- GROHE Blue single-lever faucet with filter function
- Single hole installation
- Separate handle for 3 settings of filtered and chilled drinking water: still, medium, full sparkling
- Still, medium, sparkling
- 1/2" cartridge
- GROHE StarLight finish
- GROHE SilkMove 1.4" (35 mm) ceramic cartridge
- Adjustable flow rate limiter
- Swivel Spout
- Separate internal water ways for filtered and non-filtered water
- Stainless steel flex lines
- GROHE Blue Cube
- 270 Watt cooling unit, 115 V, 60 Hz
- Type of protection IP 21
- CE approved
- GROHE Blue 600 I filter, filter head with flexible adjustment
- Max Flow Rate: 1.75 gpm (6.6 L/min)
- Only food and beverage grade or medical grade C02 can be used with the Blue C&S systems
- Grohe Blue Chilled & Sparkling cannot be used with softened water. Any water hardness measurement below 2.0 grains per gallon (35PPM) prevents carbonation.

Applicable Codes & Standards:

- Energy Policy Act of 1992
- NSF 61
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations

Color:

□ 31251DC2 SuperSteel InfinityFinish