Renew Collection
50 Inch Renew Fan WH
330100WH (White)

Product Information

Product ID	330100WH
Finish	White
Blade Finish	White/White
Collection	Renew Collection

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
Low	214	5685	87	.58	66
Med	160	4337	123	.43	35
High	70	2102	217	.23	10

Specifications

Number of Blades	5
Blades Included	Yes
Blade Pitch	12 Degrees
Blade Sweep	50"
Blades Reversible	No
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.00
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	Yes, Dual Mount Included
Lead Wire Length	78.00"
Motor Size	153MM X 15MM
Motor Type	AC

Downlight

Glass Description	N/A

Safety Listings & Certifications

Safety Rated	Dry
Energy Star	Yes
Warranty	www.kichler.com/warranty

Installation

Minimum Distance Between Bottom Of Fan Blade To Floor	7.5 feet

Dimensions

Downrod	A	B	C	D
1.00 OD X 4.00	12.75	10.50	11.75	5.90

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2

Notes:
1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER

Renew Collection
50 Inch Renew Fan WH
330100WH (White)

Finish	Fixture	Glass	Blade 1	Blade 2
Brushed Stainless Steel	330100BSS	N/A	DARK OAK	MEDIUM OAK
Brushed Nickel	330100NI	N/A	LIGHT CHERRY	WALNUT
Oil Brushed Bronze	330100OBB	N/A	LIGHT CHERRY	WALNUT
Tannery Bronze	330100TZ	N/A	TEAK	DARK CHERRY
White	330100WH	N/A	WHITE	WHITE
Matte White	330100MWH		MATTE WHITE	WEATHR WHT WLNT
Sterling Gold	330100SGD		WALNUT	STERLING GOLD

Control Options

Product ID	Descr
337001WH	Universal Remote Control
337012ALM	4 Speed Fan Slide Control
337012IV	4 Speed Fan Slide Control
337012WH	4 Speed Fan Slide Control
337214	Limited Function Cooltouch
370039MUL	Wall Control System L-Function
370040	4 Speed Rotary Switch 10 AMP

Notes:
1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER