Renew Patio Collection
52 Inch Renew Patio Ceiling Fan SBK
339515SBK (Satin Black)

Product Information

Product ID	339515SBK
Finish	Satin Black
Blade Finish	Satin Black/Non-Reversible
Collection	Renew Patio Collection

Airflow, Power and Efficiency

Speed	RPM	CFM	CFM/ Watt	Amps	Watts
Low	195	5717	85	.58	67
Med	138	4179	128	.41	33
High	65	2147	205	.24	10

Specifications

Number of Blades	5
Blades Included	Yes
Blade Pitch	12 Degrees
Blade Sweep	52"
Blades Reversible	No
Blade Material	ABS
Optional Blades Available	No
Downrod 1	1.00 OD X 4.00
Downrod 2	FLUSHMOUNT
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	No
Low Ceiling Adaptable	Yes, Dual Mount Included
Lead Wire Length	78.00"
Motor Size	153MM X 15MM
Motor Type	AC

Dimensions

Downrod	A	B	C	D
1.00 OD X 4.00	12.34	10.00	11.75	5.90

Downlight

Glass Description	N/A

Safety Listings & Certifications

Safety Rated	Wet
Energy Star	Yes
Warranty	www.kichler.com/warranty

Installation

Minimum Distance Between Bottom Of Fan Blade To	7.5 feet

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2

Notes:
1) Information provided is subject to change without notice.
All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®

Renew Patio Collection
52 Inch Renew Patio Ceiling Fan SBK
339515SBK (Satin Black)

White	339515WH	N/A	WHITE	NON-REVERSIBLE
Satin Black	339515SBK	N/A	SATIN BLACK	NON-REVERSIBLE
Tannery Bronze Powder Coat	339515TZP	N/A	BROWN	NON-REVERSIBLE
Matte White	339515MWH		MATTE WHITE	NON-REVERSIBLE

Control Options

Product ID	Descr
337214	Limited Function Cooltouch
370039MUL	Wall Control System L-Function

Notes:
1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®