

KOHLER®

Roughing-In

K-1157-CN
PROFLEX® 7236
CUSTOM WHIRLPOOL BATH

Product Information

| | | | |
|---|--------------------------------------|----|-----------|
| Applicable product: | | | |
| Custom whirlpool bath | | | K-1157-CN |
| Fixture*: | | | |
| Bathing well: | | | |
| Basin area, bottom | 55" (1397 mm) x 21" (533 mm) | | |
| Basin area, top | 65" (1651 mm) x 26" (660 mm) | | |
| Weight | 66 lbs (29.9 kg) | | |
| To overflow: | | | |
| Water depth | 15" (381 mm) | | |
| Capacity | 72 gal (272.5 L) | | |
| * Approximate measurements for comparison only. | | | |
| | | | |
| Drop-in cutout | 70-1/2" (1791 mm) x 34-1/2" (876 mm) | | |
| | | | |
| Pump: | V | Hz | A |
| 1-speed | 120 | 60 | 7.5 |

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 39 lbs/square foot (188 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

