

KOHLER®

Roughing-In

K-1139, K-1139-L, K-1139-R
PROFLEX® 6036
WHIRLPOOL BATH

Product Information

| | |
|---|----------|
| Applicable products: | |
| Whirlpool bath – drop-in (shown) | K-1139 |
| Whirlpool bath – tile flange, left drain | K-1139-L |
| Whirlpool bath – tile flange, right drain | K-1139-R |

| | |
|---|------------------------------|
| Fixture*: | |
| Bathing well: | |
| Basin area, bottom | 46" (1168 mm) x 15" (381 mm) |
| Basin area, top | 55" (1397 mm) x 25" (635 mm) |
| Weight | 55 lbs (25 kg) |
| To overflow: | |
| Water depth | 14" (356 mm) |
| Capacity | 57 gal (216 L) |
| * Approximate measurements for comparison only. | |

| | |
|----------------|--------------------------------------|
| Drop-in cutout | 58-1/2" (1486 mm) x 34-1/2" (876 mm) |
|----------------|--------------------------------------|

| | | | |
|---------|-----|----|-----|
| Pump: | V | Hz | A |
| 1-speed | 120 | 60 | 7.5 |

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (181 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

This fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677)

