

KOHLER®

Roughing-In

K-1139-CN
PROFLEX® 6036
CUSTOM WHIRLPOOL BATH

Product Information

Applicable product:			
Custom whirlpool bath - drop-in	K-1139-CN		
Fixture*:			
Bathing well:			
Basin area, bottom	46" (1168 mm) x 15" (381 mm)		
Basin area, top	55" (1397 mm) x 25" (635 mm)		
To overflow:			
Water depth	14" (356 mm)		
Capacity	57 gal (215.8 L)		
Weight	55 lbs (24.9 kg)		
* Approximate measurements for comparison only.			
Drop-in cutout	58-1/2" (1486 mm) x 34-1/4" (876 mm)		
Pump:	V	Hz	A
1-speed	120	60	7.5
Recommended accessories:			
Cable drain with PVC tubing			K-7213
Cable drain without PVC tubing			K-7214
Trip lever drain			K-11677

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (181 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

No change in measurements if connected with drain illustrated. (K-11677)

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

