

Product Information

Applicable product:				
Custom whirlpool bath with heater – drop-in			K-1139-HN	
Fixture*:				
Bathing well:				
Basin area, bottom		46" (1168 mm) x 15" (381 mm)		
Basin area, top		55" (1397 mm) x 25" (635 mm)		
Weight		60 lbs (27.2 kg)		
To overflow:				
Water depth		14" (356 mm)		
Capacity		57 gal (215.8 L)		
* Approximate measurements for comparison only.				
Drop-in cutout		58-1/2" (1486 mm) x 34-1/2" (876 mm)		
Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (183 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

