

# KOHLER®

## Roughing-In

## K-1146-H PROFLEX® 6040 WHIRLPOOL BATH WITH HEATER

### Product Information

Applicable product:				
Whirlpool bath with heater – drop-in		K-1146-H		
Fixture*:				
Bathing well:				
Basin area, bottom	46" (1168 mm) x 19" (483 mm)			
Basin area, top	55" (1397 mm) x 29" (737 mm)			
Weight	61 lbs (27.7 kg)			
To overflow:				
Water depth	14" (356 mm)			
Capacity	54 gal (204.4 L)			
* Approximate measurements for comparison only.				
Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	KW	V	Hz	A
	1.5	120	60	12.5
* Approximate measurement for comparison only.				
Included components:				
Cutout template			114859-7	

### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 33 lbs/square foot (158 kg/square meter) loading.

The suction line extends 1" (25 mm) beyond the edge of the rim. The pump base extends 1-1/8" (29 mm) beyond the edge of the rim. Modify the framing as needed.

This fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677)

