

KOHLER®

Roughing-In

K-1146-CK, K-1146-CN
PROFLEX® 6040
CUSTOM WHIRLPOOL BATH

Product Information

Applicable products:			
Custom whirlpool bath			K-1146-CK
Custom whirlpool bath			K-1146-CN
Fixture*:			
Bathing well:			
Basin area, bottom		46" (1168 mm) x 19" (483 mm)	
Basin area, top		55" (1397 mm) x 29" (737 mm)	
Weight		56 lbs (25.4 kg)	
To overflow:			
Water depth		14" (356 mm)	
Capacity		54 gal (204.4 L)	
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5
Included components:			
Cutout template			114859-7

Required Electrical Service

Dedicated circuit required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 32 lbs/square foot (156 kg/square meter) loading.

NOTICE: The pump must be relocated to its custom position at the time of installation. Provide adequate clearance between the floor and the pump.

This fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with the drain illustrated. (K-11677)

