



# Underscore® 5" Bubblemassage™ Whirlpool Bath K-1167-XH2GL



## Features

- Left drain.
- Flange helps prevent water from seeping behind wall and simplifies alcove installation.
- Integral lumbar support and armrests for comfort.
- Slotted overflow allows for deep soaking.
- 60" (1524 mm) x 30" (762 mm) x 19" (483 mm)

## Material

- Acrylic

## Hydrotherapy

- Automatic purge cycles remove residual water from air channels after use.
- 118-122 BubbleMassage™ airjets.
- Variable-speed blower lets you adjust airjet massage intensity to 18 levels.
- Variable-speed pump for adjusting hydromassage intensity.
- Zones of Control™ feature allows you to target airjet massage to back, midsection, or feet.
- Single-speed whirlpool offers eight fully adjustable hydro-massage jets for water flow and direction.
- Pump with air switch for whirlpool.
- Built-in 1500 W heater.

## Installation

- Three-wall alcove.

## Required Accessories

K-7271 Brass Slotted Overflow Bath Drain

or

K-9698 Flexjet® Whirlpool Trim Kit

## Recommended Accessories

K-1491 Bath/Whirlpool Pillow

K-1601 Bath/Whirlpool Footstop

K-9497 2-1/2" Keypad Trim

K-24916 Wireless Music Kit

K-7272 PVC Slotted Overflow Bath Drain



## Codes/Standards

ASME A112.19.7/CSA B45.10

CSA B45.5/IAPMO Z124

ASTM E162

ASTM E662

UL 1795

CSA 22.2 No. 218.2











Greenguard UL 2818 - Gold

## KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

## Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™


USA/Canada: 1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to [www.kohler.com](http://www.kohler.com).

1-13-2017 03:42

THE BOLD LOOK  
OF **KOHLER**®



Blower, Pump, 220-240 V, 20 A, 50/60 Hz  
Heater:

All product dimensions are nominal.

Installation:	3-Wall Alcove, Under-mount
Drain location:	Left
Basin area, bottom:	42-7/16" x 20" (1078 mm x 508 mm)
Basin area, top:	54-5/16" x 24-1/4" (1380 mm x 616 mm)
Weight:	157 lbs (71.2 kg)
Minimum floor load:	53.9 lbs/ft <sup>2</sup> (263.2 kg/m <sup>2</sup> )
Water depth:	15-1/8" (384 mm)
Water capacity:	59.8 gal (226.4 L)
Electrical component rating:	Blower: 220-240 V, 5 A, 50/60 Hz, 300 W Pump: 220-240 V, 11 A, 50/60 Hz Heater: 220-240 V, 50/60 Hz, 1500 W
Minimum flat for door:	1-15/16" (49 mm)

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

This unit is not intended for flush-mount apron installation.

**IMPORTANT!** Dry fit the drain assembly prior to installing the bath. The bath cannot be installed with all drain components attached.

The pump base extends 10-1/4" (260 mm) beyond the edge of the rim. Modify the framing as needed.