

### Features

- Vitreous china.
- Elongated bowl.
- AquaPiston® flushing system.
- One-piece.
- Includes seat and cover.
- Includes trip lever.
- Less supply.
- 1.28 gpf (4.8 lpf).
- 12" (305 mm) rough-in.
- 2-1/8" (54 mm) glazed trapway.
- 11" (279 mm) x 8-3/4" (222 mm) water area.
- 28-1/8" (714 mm) x 17-3/4" (451 mm) x 28-5/8" (727 mm).

### Optional Accessories

K-4650 Toilet Seat  
 K-1954 Touchless Toilet Flush Kit  
 K-4008 Toilet Seat  
 K-4636 Toilet Seat  
 K-4652 Toilet Seat  
 K-4659 Toilet Seat  
 K-4684 Toilet Seat  
 K-4688 Toilet Seat  
 K-4694 Toilet Seat  
 K-4709 Toilet Seat with Cleansing Functionality  
 K-4713 Toilet Seat  
 K-4732 Toilet Seat  
 K-4733 Toilet Seat  
 K-4748 Toilet Seat  
 K-4774 Toilet Seat  
 K-4814 Toilet Seat  
 K-4888 Elongated Toilet Seat  
 K-5588 Elongated Toilet Seat  
 K-5638 Elongated Toilet Seat  
 K-7637 Angle Supply with Stop (single)  
 K-4712-T Toilet Seat  
 K-4761-BN Toilet Seat  
 K-4761-CP Toilet Seat  
 K-9167-R Trip Lever

### Components

Product includes:

K-4733 Toilet Seat

Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Tank accessory pack.



ADA

CSA B651

OBC

### Codes/Standards

ASME A112.19.2/CSA B45.1  
 DOE - Energy Policy Act 1992  
 EPA WaterSense®  
 ADA  
 ICC/ANSI A117.1  
 CSA B651  
 OBC




### KOHLER® One-Year Limited Warranty


See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

#### Color Code Description

	0	White
	96	Biscuit
	47	Almond



## Technical Information

All product dimensions are nominal.

Toilet type:	One-piece, Floor-mount
Waste Outlet:	Floor
Bowl shape:	Elongated front
Flush type:	AquaPiston
Seat hinge type:	Quiet-Close™, Quick-Release™
Trap passageway:	2-1/8" (54 mm)
Water Consumption	
Full:	1.28 gpf (4.8 lpf)
Water surface size:	11" x 8-3/4" (279 mm x 222 mm)
Rim to water surface:	6" (152 mm)
Rough-in:	12" (305 mm)
Seat-mounting holes:	5-1/2" (140 mm)

## Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

The Model Plumbing Codes require the installation of elongated open-front toilet seats on public bathrooms.