

# **Memoirs®**

# Comfort Height® Toilet K-3817-U

#### **Features**

- Vitreous china.
- Two-piece toilet.
- Comfort Height® Elongated bowl.
- AquaPiston® flushing system.
- Includes left-hand polished chrome trip lever.
- 1.28 gpf (4.8 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 12" (305 mm) rough-in.
- Less seat and supply.
- 11-3/4" (298 mm) x 9-1/2" (241 mm) water area.
- 30-3/8" (772 mm) x 18-7/8" (479 mm) x 31-1/16" (789 mm).
- Floor mount / Floor outlet.
- Insuliner® tank liner included.

## **Optional Accessories**

K-9167-L Trip Lever

K-4650 Toilet Seat

K-4108 Toilet Seat with Cleansing Functionality

K-4636 Toilet Seat

K-4652 Toilet Seat

K-4659 Toilet Seat

K-4684 Toilet Seat

K-4688 Toilet Seat

K-4694 Toilet Seat

K-4709 Toilet Seat with Cleansing Functionality

K-4733 Toilet Seat

K-4737 Toilet Seat with Cleansing Functionality

K-4748 Toilet Seat

K-4774 Toilet Seat

K-4814 Toilet Seat

K-5588 Elongated Toilet Seat

K-7637 Angle Supply with Stop (single)

K-4712-T Toilet Seat

K-4761-BN Toilet Seat

K-4761-CP Toilet Seat

## Components

Product includes:

K-4380 Toilet Bowl

K-4434-U Toilet Tank

Additional included component/s: Tank cover, Trip lever, Bolt

cap accessory pack, and Tank accessory pack.





## Codes/Standards

OBC

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651

## **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

## **Available Color/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	7	Black Black <sup>TM</sup>






## **Memoirs®**

# Comfort Height® Toilet

K-3817-U



## **Technical Information**

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Floor

Bowl shape: Elongated front Flush type: AquaPiston Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.28 gpf (4.8 lpf)

Water surface size: 11-3/4" x 9-1/2" (298 mm x 241 mm)

Rim to water surface: 6-1/8" (156 mm)

Rough-in: 12" (305 mm)

Seat-mounting holes: 5-1/2" (140 mm)

#### **Notes**

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

The Model Plumbing Codes require the installation of elongated open-front toilet seats on public bathrooms.

