



**Wellworth®**  
Class Five® Toilet  
**K-3998**

### Features

- Vitreous china.
- Two-piece toilet.
- Regular height Elongated bowl.
- Class Five® flushing system.
- Includes left-hand polished chrome trip lever.
- 1.28 gpf (4.8 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 12" (305 mm) rough-in.
- Less seat and supply.
- 11-1/4" (286 mm) x 8-1/4" (210 mm) water area.
- 30" (762 mm) x 18" (457 mm) x 29-1/4" (743 mm).
- Floor mount / Floor outlet.

### Optional Accessories

K-1954 Touchless Toilet Flush Kit  
K-4008 Toilet Seat  
K-4108 Toilet Seat with Cleansing Functionality  
K-4636 Toilet Seat  
K-4652 Toilet Seat  
K-4659 Toilet Seat  
K-4684 Toilet Seat  
K-4688 Toilet Seat  
K-4694 Toilet Seat  
K-4709 Toilet Seat with Cleansing Functionality  
K-4737 Toilet Seat with Cleansing Functionality  
K-4748 Toilet Seat  
K-4774 Toilet Seat  
K-4814 Toilet Seat  
K-5588 Elongated Toilet Seat  
K-5638 Elongated Toilet Seat  
K-7637 Angle Supply with Stop (single)  
K-9379 Trip Lever  
K-4712-T Toilet Seat  
K-4761-BN Toilet Seat  
K-4761-CP Toilet Seat

### Components

Product includes:

K-4198 Elongated Bowl  
K-4467 Toilet Tank

Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Tank accessory pack.



### Codes/Standards





ASME A112.19.2/CSA B45.1  
DOE - Energy Policy Act 1992  
EPA WaterSense®


### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	7	Black Black™



## Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Floor-mount

Waste Outlet: Floor

Bowl shape: Elongated front

Flush type: Class Five

Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.28 gpf (4.8 lpf)

Water surface size: 11-1/4" x 8-1/4" (286 mm x 210 mm)

Rim to water surface: 5-1/4" (133 mm)

Rough-in: 12" (305 mm)

Seat-mounting holes: 5-1/2" (140 mm)

## Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.